

BUF-02A Fujioh-Blower unit Individual Specifications			
Model		BUF-02A (WH, BK, BIS, SM, SUS)	
Dimension inch	Width	19-11/16"	
	Height	7-1/2"	
	Depth	13-11/16"	
Weight	lbs	18	
Rated Voltage	V	120	
Rated Frequency	Hz	60	
Air-flow (at 0pa/ 25Pa)	CFM	Hi	370 CFM / 350 CFM – (6" round duct / Upper Exhaust Direction)
		Me	230 CFM / 210CFM – (6" round duct / Upper Exhaust Direction)
		Lo	150 CFM / 1300CFM – (6" round duct / Upper Exhaust Direction)
Noise Level	Sones / dB	Hi	7.0 / 56.0 - (6" round duct / Upper Exhaust Direction)
		Me	3.0 / 44.5 - (6" round duct / Upper Exhaust Direction)
		Lo	1.5 / 34.5 - (6" round duct / Upper Exhaust Direction)
Power Consumption	W	Hi	220±10%
		Me	140±10%
		Lo	105±10%
		Note: The power consumption is indicated without the 50W light bulb	
Electric Motor		Single phase capacitor motor 3 speed, Insulation = A, Pole = 4, Open type	
Duct Dimension		φ6" Round Duct	
Back Draft Damper		Yes	
Exhaust Direction		Vertical only	
Installation		At 4 places on the flange of the body, use screws and nut plates for mounting to the Liner.	
Material Finish	Front Cover	Zinc sheet or Stainless steel / polyester resin powder coating	
	Rear Cover	Zinc sheet	
	Fan unit	Zinc sheet	
	Fan	Zinc sheet, Sirocco Fan	
	Filter	Aluminium alloy / Single-Slot Filter	
Colour tone	Front Cover	WH: White (1GY9/0.5), BK: Black (2BG1.5/0.5), BIS: Biscuit (5Y8.25/1), SM: Silver Metallic, SUS: Hair Line Finish with Clear Powder Coating	
Switch		Mechanical Push button switch with Pilot lamp (OFF/ Lo/ Me/ Hi/ LIGHT)	
Light		One location, Light bulb rating up to 50W is available (base: GU10) Note: Light bulb is not included inside the carton.	
Electric wiring cord (Material etc.)		Vinyl chloride tunic, cut-off area = over 18AWG	
Accessory		Screws, Nut-plates	
Optional parts		Metal Liners (The Liner is various; Rectangular, Standard, T-shaped, Peninsula), Ductless Conversion Kit	
Manual		Operation manual, Installation manual	