

BUF-04 (J) Fujioh-Blower unit Individual Specifications			
Model		BUF-04 (J) (WH, BK, BIS, SM)	
Dimension inch	Width	19-11/16"	
	Height	3-15/16"	
	Depth	13-11/16"	
Weight	lbs	8.0	
Rated Voltage	V	120	
Rated Frequency	Hz	60	
Air-flow (at 0pa/ 25Pa)	CFM	Hi	320 CFM / 260 CFM – (7" round duct / Upper Exhaust Direction)
		Lo	300 CFM / 210 CFM – (7" round duct / Upper Exhaust Direction)
Noise Level	Sones / dB	Hi	6.5 / 58.2 - (7" round duct / Upper Exhaust Direction)
		Lo	4.5 / 56.7 - (7" round duct / Upper Exhaust Direction)
Power Consumption	W	Hi	30 ± 10%
		Lo	28 ± 10%
	Note: The power consumption is indicated without the 40W light bulb		
Electric Motor		Single phase capacitor motor 2 speed, Insulation = A, Pole = 2, Closed type	
Duct Dimension		ϕ 7" Round Duct	
Back Draft Damper		Yes	
Exhaust Direction		Vertical only	
Installation		At 4 places on the flange of the body, use screws and nut plates for mounting to the Liner.	
Material Finish	Front Cover	Zinc sheet / polyester resin powder coating	
	Rear Cover	Zinc sheet	
	Fan	Plastic, Axial Fan	
	Filter	Aluminium alloy / Single-Slot Filter	
Colour tone	Front Cover	WH: White (1GY9/0.5), BK: Black (2BG1.5/0.5), BIS: Biscuit (5Y8.25/1), SM: Silver Metallic	
Fan Switch		Rocker switch (Hi/ Off/ Lo)	
Lamp Switch		Rocker switch (On/ Off)	
Light		One location, Light bulb rating up to 40W is available (base:E17) Note: Light bulb is not included inside the carton.	
Electric wiring cord (Material etc.)		Vinyl chloride tunic, cut-off area = over 18AWG	
Accessory		Screws, Nut-plates, Damper	
Optional parts		Metal Liners, Ductless Conversion Kit	
Manual		Operation manual, Installation manual	