

BUF-06E Fujioh-Blower unit Individual Specifications			
Model		BUF-06E (SUS)	
Dimension inch	Width	27"	
	Height	15-9/16"	
	Depth	16-7/8"	
Weight	lbs	11.0	
Rated Voltage	V	120	
Rated Frequency	Hz	60	
Air-flow (at 0pa/ 25Pa)	CFM	Hi	-
		Me	-
		Lo	-
Noise Level	Sones / dB	Hi	8.0 / 56.0 - (7" round duct / Upper Exhaust Direction)
		Me	- / 45.0 - (7" round duct / Upper Exhaust Direction)
		Lo	- / 31.0 - (7" round duct / Upper Exhaust Direction)
Power Consumption	W	100W for Two 50W lamps	
		Note: The power consumption is indicated Two 50W light bulbs	
Electric Motor		-	
Duct Dimension		ϕ 10" Round Duct	
Back Draft Damper		Yes	
Exhaust Direction		Vertical only	
Installation		At 4 places on the flange of the body, use screws and nut plates for mounting to the Liner.	
Material Finish	Front Cover	Stainless Steel / Clear powder coating	
	Rear Cover	Zinc sheet	
	Fan unit	-	
	Fan	-	
	Filter	Aluminium alloy / Single-Slot Filter	
Colour tone	Front Cover	SUS: Hair Line Finish with Clear Powder Coating	
Switch		Mechanical Push button switch (ON/OFF)	
Light		Two locations, Light bulb rating up to 50W is available (PAR20, E26) Note: Light bulb is not included inside the carton.	
Electric wiring cord (Material etc.)		Vinyl chloride tunic, cut-off area = over 18AWG	
Accessory		Screws, Nut-plates	
Optional parts		Metal Liners (The Liner is various; Rectangular, Standard, T-shaped)	
Manual		Operation manual, Installation manual	