

BUF-06P Fujioh-Blower unit Individual Specifications			
Model		BUF-06P (SUS)	
Dimension inch	Width	27"	
	Height	15-9/16"	
	Depth	16-7/8"	
Weight	lbs	37.4	
Rated Voltage	V	120	
Rated Frequency	Hz	60	
Air-flow (at 0pa/ 25Pa)	CFM	Hi	650 CFM / 620 CFM – (7" round duct / Upper Exhaust Direction)
		Me	430 CFM / 410 CFM – (7" round duct / Upper Exhaust Direction)
		Lo	230 CFM / 210 CFM – (7" round duct / Upper Exhaust Direction)
Noise Level	Sones / dB	Hi	7.5 / 56.0 (7" round duct / Upper Exhaust Direction)
		Me	- / 45.0 (7" round duct / Upper Exhaust Direction)
		Lo	- / 32.0 (7" round duct / Upper Exhaust Direction)
Power Consumption	W	Hi	225±10%
		Me	160±10%
		Lo	120±10%
		Note: The power consumption is indicated without the Two 50W light bulbs	
Electric Motor		Single phase capacitor motor 3 speed, Insulation = A, Pole = 4, Close type	
Duct Dimension		φ 7" Round Duct	
Back Draft Damper		Yes	
Exhaust Direction		Vertical only	
Installation		At 4 places on the flange of the body, use screws and nut plates for mounting to the Liner.	
Material Finish	Front Cover	Stainless Steel / Clear powder coating	
	Rear Cover	Zinc sheet	
	Fan unit	Zinc sheet	
	Fan	Zinc sheet, Sirocco Fan, Clear Power Coated	
	Filter	Aluminium alloy / Single-Slot Filter	
Colour tone	Front Cover	SUS: Hair Line Finish with Clear Powder Coating	
Switch		Mechanical Push button switch with Pilot lamp (OFF/Lo/Me/Hi/LIGHT)	
Light		Two locations, Light bulb rating up to 50W is available (PAR20, E26) Note: Light bulb is not included inside the carton.	
Electric wiring cord (Material etc.)		Vinyl chloride tunic, cut-off area = over 18AWG	
Accessory		Screws, Nut-plates, Mounting Bracket	
Optional parts		Metal Liners (The Liner is various; Rectangular, Standard, T-shaped, Peninsula)	
Manual		Operation manual, Installation manual	