

BUF-08P Fujioh-Blower unit Individual Specifications			
Model		BUF-08P (SUS)	
Dimension inch	Width	45"	
	Height	14-5/8"	
	Depth	17-7/8"	
Weight	lbs	70.5	
Rated Voltage	V	120	
Rated Frequency	Hz	60	
Air-flow (at 0pa/ 25Pa)	CFM	Hi	1250 CFM / 1210 CFM – (7" round duct / Upper Exhaust Direction)
		Me	830 CFM / 790CFM – (7" round duct / Upper Exhaust Direction)
		Lo	450 CFM / 390 CFM – (7" round duct / Upper Exhaust Direction)
Noise Level	Sones / dB	Hi	8.5 / 58.0 - (7" round duct / Upper Exhaust Direction)
		Me	- / 47.0 - (7" round duct / Upper Exhaust Direction)
		Lo	- / 32.0 - (7" round duct / Upper Exhaust Direction)
Power Consumption	W	Hi	700±10%
		Me	500±10%
		Lo	420±10%
		Note: The power consumption is indicated without the Three 50W light bulb	
Electric Motor		Single phase capacitor motor 3 speed, Insulation = A, Pole = 4, Close type	
Duct Dimension		2x ϕ 7" Round Duct	
Back Draft Damper		Yes	
Exhaust Direction		Vertical only	
Installation		At 4 places on the flange of the body, use screws and nut plates for mounting to the Liner.	
Material Finish	Front Cover	Stainless Steel / Clear powder coating	
	Rear Cover	Zinc sheet	
	Fan unit	Zinc sheet	
	Fan	Zinc sheet, Sirocco Fan, Clear Power Coated	
	Filter	Aluminium alloy / Single-Slot Filter	
Colour tone	Front Cover	SUS: Hair Line Finish with Clear Powder Coating	
Switch		Dual Control: Mechanical Push button switch with Pilot lamp (OFF/Lo/Me/Hi/LIGHT)	
Light		Variable Control by Dimmer Switch Three location, Light bulb rating up to 50W is available (PAR20, E26) Note: Light bulb is not included inside the carton.	
Electric wiring cord (Material etc.)		Vinyl chloride tunic, cut-off area = over 18AWG	
Accessory		Screws, Nut-plates, Installation Board	
Optional parts		Metal Liners (The Liner is various; Rectangular, Standard, T-shaped, Peninsula)	
Manual		Operation manual, Installation manual	