

EBW-Series		Fujioh-Range hood (Ducted-type) Individual Specifications			
Model		EBW-300SUS with EBW3024	EBW-300SUS with EBW3030	EBW-360SUS with EBW3624	EBW-360SUS with EBW3630
Dimension inch	Width	30"	30"	36"	36"
	Height	24"	30"	24"	30"
	Depth	19"	19"	19"	19"
Weight	lbs	40.2	41.9	43.2	45.1
Rated Voltage	V	120			
Rated Frequency	Hz	60			
Air-flow (at 0Pa / 25Pa)	CFM	Hi	380CFM / 350 CFM		
		Me	220CFM / 200 CFM		
		Lo	150CFM / 120 CFM		
Noise Level	Sones / dB(A)	Hi	6.6 / 55.5		
		Me	2.8 / 43.0		
		Lo	1.8 / 33.0		
Power Consumption	W	Hi	170±10%		
		Me	100±10%		
		Lo	55±10%		
		Note: The power consumption is indicated without the two 40W light bulbs			
Electric Motor		Single phase capacitor motor 3 speed, Insulation = A, Pole = 4, open type			
Duct Dimension (mm)		6" Round Duct Upper Exhaust			
Back Draft Damper		Yes			
Exhaust Direction		Vertical			
Installation		Use wood screws at 6 places on the backside of the body			
Material Finish	Front Panel	Stainless Steel SUS304			
	Back Parts	Stainless Steel SUS304			
	Fan unit	Zinc sheet			
	Fan	Zinc sheet, Sirocco Fan			
	Filter	Aluminium alloy / Single-Slot Filter			
	Duct Cover	Stainless Steel SUS304, Zinc sheet			
Colour tone	Front Panel / Back Parts	SUS: Stainless steel (Hair Line Finish)			
Switch		Mechanical Push button switch (OFF/Lo/Me/Hi/LIGHT)			
Light		One location, Light bulb rating up to 40W is available (base: Intermediate E17) Note: Light bulb is not included inside the carton.			
Electric wiring cord (Material etc.)		Vinyl chloride tunic, cut-off area = over 18AWG			
Accessory		Screws, Nut-plates, Back draft damper, Mounting screws			
Optional parts		None			
Manual		Operation manual, Installation manual			

Issued on Apr 25th, 2006