

EBW-600/660 Series		Fujioh-Range hood (Ducted-type) Individual Specifications			
Model		EBW-600SUS with EBW3024	EBW-600SUS with EBW3030	EBW-660SUS with EBW3624	EBW-660SUS with EBW3630
Dimension inch	Width	30"	30"	36"	36"
	Height	24"	30"	24"	30"
	Depth	19"	19"	19"	19"
Weight	lbs	53.5	55.0	56.0	58.0
Rated Voltage	V	120			
Rated Frequency	Hz	60			
Air-flow (at 0Pa / 25Pa)	CFM	Hi	640 CFM / 630 CFM		
		Me	390 CFM / 370 CFM		
		Lo	200 CFM / 170 CFM		
Noise Level	Sones / dB(A)	Hi	5.5 / 53.0	6.0 / 53.0	
		Me	3.0 / 41.0	2.5 / 41.0	
		Lo	1.0 / 30.0	1.0 / 30.0	
Power Consumption	W	Hi	170 ± 10%		
		Me	100 ± 10%		
		Lo	55 ± 10%		
		Note: The power consumption is indicated without the two 35W light bulbs			
Electric Motor		Single phase capacitor motor 3 speed, Insulation = A, Pole = 4, Closed type			
Duct Dimension (mm)		7" Round Duct Upper Exhaust			
Back Draft Damper		Yes			
Exhaust Direction		Vertical			
Installation		Use wood screws at 4 places on the backside of the body			
Material Finish	Front Panel	Stainless Steel SUS304			
	Back Parts	Stainless Steel SUS304			
	Fan unit	Zinc sheet			
	Fan	Zinc sheet, Sirocco Fan			
	Filter	Aluminium alloy / Single-Slot Filter			
Colour tone	Front Panel / Back Parts	SUS: Stainless steel (Hair Line Finish)			
Switch		Mechanical Push button switch (OFF/Lo/Me/Hi/LIGHT)			
Light		Two location, Light bulb rating up to 35W is available (Shape: MR16, base: GU10) Note: Light bulb is not included inside the carton.			
Electric wiring cord (Material etc.)		Vinyl chloride tunic, cut-off area = over 18AWG			
Accessory		Screws, Back draft damper, Mounting screws			
Optional parts		Front part (Purchase separatory: EBW-3024, 3030, 3624, 3630)			
Manual		Operation manual, Installation manual			