

ECW-360SUS Fujioh-Range hood (Ducted-type) Individual Specifications			
Model		ECW-360SUS	
Dimension inch	Width	36"	
	Height	33" – 46-7/8"	
	Depth	24"	
Weight	lbs	32	
Rated Voltage	V	120	
Rated Frequency	Hz	60	
Air-flow (at 0Pa / 25Pa)	CFM	Hi	620CFM / 600 CFM
		Me	360CFM / 350 CFM
		Lo	180CFM / 160 CFM
Noise Level	Sones / dB	Hi	6.2 / 50.5
		Me	4.0 / 39.5
		Lo	1.8 / 25.0
Power Consumption	W	Hi	230±10%
		Me	155±10%
		Lo	120±10%
		Note: The power consumption is indicated without the two 50W light bulbs	
Electric Motor		Single phase capacitor motor 3 speed, Insulation = A, Pole = 4, Closed type	
Duct Dimension (mm)		7" Round Duct Upper Exhaust	
Back Draft Damper		Yes	
Exhaust Direction		Vertical	
Installation		Use wood screws at 6 places on the backside of the body	
Material Finish	Hood	Stainless Steel SUS304	
	Fan unit	Zinc sheet	
	Fan	Zinc sheet, Sirocco Fan, Clear coated	
	Filter	Aluminium alloy / Single-Slot Filter	
	Duct Cover	Stainless Steel SUS304, Zinc sheet	
Colour tone	Hood / Duct Cover	SUS: Stainless steel (Hair Line Finish)	
Switch		Mechanical Push button switch (OFF/Lo/Me/Hi/LIGHT)	
Light		Two location, Halogen lamp rating up to 50W is available (base: Medium E26) Note: Halogen lamp is not included inside the carton.	
Electric wiring cord (Material etc.)		Vinyl chloride tunic, cut-off area = over 18AWG	
Accessory		Screws, Nut-plates, Back draft damper, Mounting screws	
Optional parts		Trim Ring	
Manual		Operation manual, Installation manual	